

HY-6800H

Barcode scanner

1D Red Light Wired



Features:



Red Light
Quick identification



Screen barcode
Various 1D barcodes



Drop-resistant
sturdy and durable



Plug and Play
Wired connection

Application: Retail, warehousing and logistics, office, etc



HY-6800H 1D Red Light Wired

Parameter :

Performance Characteristics	
Light Source	630nm±10nm
Scanning speed	300 times / sec
Resolution	1500 dpi
CPU	32-BIT
Skew/Yaw	Skew ±60° / Yaw ±60°
Interface support	USB、RS232
Printing Contrast	30%minimum reflective difference
Decode Capability	
1D	EAN13, EAN-8, UPC-A, Code39, Code93, Code128, codabar(nw-7), ISSN,ISBN,GS1 Databar, GS1-128 Composite Code, Code 11, Industrial 25 ,MSI Plessey , etc,ITF-6,ITF-14, Rss, China Post, interleaved 2 of 5...
User Environment	
Operating Temperature	-20℃~+50℃
Storage Temperature	-40℃~+70℃
Humidity	0%~95% Relative humidity, non-condensing
Seismic resistance	Designed to withstand 1.5m(6) drops
Ambient Lighting	300 LUX
Decode Ranges	
EAN-13	13mil 70-400mm
Code39	5mil 70-130mm (EAN-13 4 byte)
1D Minimum resolution	≥4.5mil
Physical Characteristics	
Dimensions	(L) 170mm* (W) 68mm* (H) 90mm
Weight	Scanner 135g Packing120g
Input Voltage, Operating Voltage	DC5V, DC3.3V
Operating Current, Standby Current	70mA, 10mA
Application scope	
Express Logistics Supermarket chain Manufacture An institution etc	

