

# HY-6709M

## Barcode scanner with phone holder

Warehouse Inventory Data Real-time Synchronization




[Wired/Wireless 2.4G + Bluetooth/With or without stand]




### Features:



Scan sensitivity  
500,000-pixel global



Accurate code  
reading



Mobile office work  
Efficient and quick



Bluetooth + Wireless  
Convenient and quick

### Applications:

Suitable for logistics / warehousing / supermarket / inventory



## Performance Parameters:

Performance Characteristics	
Sensor pixel	500,000 pixels
Scan speed	300per second
Recognition accuracy	≥4MIL
Light Source	Aiming630nm LED; illumination:6500K LED
Print contrast	≥25%minimum reflective difference
Rotation tilt deviation	360°,±55°,±55°
Radio frequency	2.4G~2.483 GHZ Bluetooth compatible 5.0
Wireless distance	50M (Open Range)
Bluetooth distance	15-30米 (Open Range)
Memory	4Mb
Scanning method	Manual/Continuous/Self-inductive
Decode Capability	
1-D	EAN13,EAN-8,UPC-A,Code39,Code93,Code128,codabar(nw-7),ISSN, ISBN,GS1-Databar,GS1-128 Composite Code,Code 11,Industrial 25 ,MSI Plessey , etc,ITF-6,ITF-14, Rss ,China Post,interleaved 2 of 5
/2-D	QR Code, Data Matrix,Maxicode, PDF417,Aztec, Maxicode, Hanxin,Etc.
User Environment	
Operating Temperature	-20℃~+50℃
Storage Temperature	-40℃~+70℃
Storage Temperature	5%~95%relative humidity,non-condensing
Seismic resistance	Designed to withstand 1.5m(6)drops
Ambient Lighting	0~100000LUX
Decode Ranges	
EAN-13	50mm-150mm (13mil)
Code39	40mm-120mm (5mil 10byte)
QR Code	25mm-180mm (20mil 16byte)
Data Marix	50mm-90mm (10mil 20byte)
PDF 417	30mm-90mm (6.67mil 7byte)
1D Minimal resoluton	4-5mil
2D Minimal resoluton	≥4.5mil
Physical Characteristics	
Dimensions	170(L)*68(W)*90(H)mm
Weight	scanner185g Packing120g
Input Voltage, Operating Voltage	DC5V, DC3.3V
Operating Current, Standby Current	220MA, 25MA
Application scope	
Express Logistics Supermarket chain Manufacture An institution etc	

