


# HY-T6900 Barcode scanner 1D Laser Wired



## Features:



High-end laser  
High-speed reading



Accurate scanning  
efficient work



Drop-resistant  
sturdy and durable



Plug and Play  
Wired connection

## Application: Logistics, manufacturing, healthcare, retail, etc



# HY-T6900 1D Laser Wired

## Parameter

Performance Characteristics	
CPU	32-BIT
Scanning speed	380times/second
Light Source	Visual laser diode 630nm±10nm
Recognition accuracy	3MIL
Scanning angle	Corner±40°,elevation±40°,drift angle±40°
Scanning method	Manual or automatic (Optional accessories)
Interface support	USB,RS232,KB
Printing Contrast	25%minimum reflective difference
Setting Mode	Manual (scan bar code in turn)
Program update	Computer Online Update
Decode Capability	
1D	EAN13,EAN-8,UPC-A,Code39,Code93,Code128,codabar(nw-7),ISSN, ISBN,GS1-Databar,GS1-128 Composite Code,Code 11,Industrial25 ,MSI Plessey , etc,ITF-6,ITF-14, Rss ,China Post,interleaved 2 of 5..
User Environment	
Operating Temperature	-10℃~+50℃
Storage Temperature	-40℃~+60℃
Humidity	5%~95%Relative humidity,non-condensing
Seismic resistance	Designed to withstand 1.5m(6)drops
Decode Ranges	
Depth of Field and Resolution	4mil 30-65mm (EAN-13)
Depth of Field and Resolution	5mil 20-75mm (EAN-13 )
Depth of Field and Resolution	13mil,m-130mm (5mil 10byte )
Physical Characteristics	
Dimensions	(L)170mm*(W)68mm*(H)90mm
Weight	135g pack120g
Input Voltage, Operating Voltage	DC5V, DC3.3V
Operating Current, Standby Current	70MA, 20MA
Application scope	
Express Logistics Supermarket chain Manufacture An institution etc	

